



## RLTMRL-III-635 (round spot) / 1-150mW

### RED DIODE LASER At 635nm

Diode red laser 635nm is made features of ultra compact, long lifetime, low cost and easy operating, which is widely used in measurement, spectrum analysis, laser lighting show, etc.



#### SPECIFICATIONS

Wavelength (nm)	635 ± 5		
Output power (mW)	>1, 10, 20, ..., 150		
Energy distribution	Even		
Beam spot	Round		
Operating mode	CW		
Power stability (rms, over 4 hours)	<1%, <3%, <5%		
Warm-up time (minutes)	<5		
Beam divergence, full angle (mrad)	<8.0		
Beam diameter at the aperture (mm)	~2.0		
Beam height from base plate (mm)	24.8		
Polarization ratio	>50:1		
Pointing stability after warm-up (mrad)	<0.05		
Operating temperature (°C)	10~35		
Power supply (90-264VAC or 5VDC)	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
Expected lifetime (hours)	10000		
Warranty	1 year		



MxL-III -635	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
140.8(L) x 73(W) x 46.2(H) mm <sup>3</sup> , 0.6kg	154(L) x 155(W) x 95(H) mm <sup>3</sup> , 1.5kg	133(L) x 130(W) x 65(H) mm <sup>3</sup> , 1.2kg	100(L) x 60(W) x 56(H) mm <sup>3</sup> , 0.2kg