



ROITHNER LASERTECHNIK GmbH

WIEDNER HAUPTSTRASSE 76
TEL. +43 1 586 52 43 -O. FAX. -44

1040 VIENNA
OFFICE@ROITHNER-LASER.COM

AUSTRIA



CW532H

- Green Diode Pumped Laser Module
- 532 nm, 1-300 mW
- 3 VDC
- CE certified



Description

CW532H is a series of **green** diode pumped solid-state high power laser modules, emitting at typically **532 nm**, with 3 VDC supply voltage. It is RoHS compliant, CE certified, and comes with a **6 months warranty**. An additional external heat sink is required for operation

Electro-Optical Characteristics

Parameter	Values	Unit
Wavelength	532	nm
Output Power	1...300	mW
Operating Mode	CW	
Transverse Mode	TEM ₀₀	
Beam Divergence (full angle)	~ 1.5	mrad
Beam Diameter at the aperture (1/e ²)	~ 1.5	mm
Operating Temperature	10 - 25	°C
Supply Voltage*	3	VDC
Current Draw	<1 (100mW), <2 (300mW)	A
Expected Lifetime	10000	hours

* Housing electrically connected to + 3 VDC



Outline Dimensions


Laser module





Accessories

Heat Sink CWH-HSTEC5



- Temperature controlled heat sink
- 5 VDC
- TEC
- Thermistor
- Fan

© All Rights Reserved

The above specifications are for reference purpose only and subjected to change without prior notice